FACSIMILE COVER SHEET

Patents, Trademarks and Related Matters
Killworth, Gottman, Hagan & Schaeff, L.L.P.
One Dayton Centre
One South Main Street, Suite 500
Dayton, Ohio 45402-2023

937.223.2050
Fax | 937.223.0724
E-mail | kghs@kghs.com
www.KGHS.com

TO: Examiner Ginette Peralta

Company: Assistant Commissioner for Patents
Fax No.: 703/872-9318

FROM: Julie G. Cope, Reg. No. 48,624/amm

Date: March 21, 2003
Pages: 9
(including cover page)
Our Docket No.: MIO 0024 PA

Transmission No.: _____

☒ ORIGINAL WILL NOT FOLLOW

☐ ORIGINAL WILL FOLLOW BY: ☐ REGULAR MAIL ☐ EXPRESS MAIL

Remarks:

U.S. Patent Application Serial No. 08/915,658

OFFICIAL ***OFFICIAL*** ***OFFICIAL***

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application of

Applicant	: Jigish D. Trivedi
Serial No.	: 08/915,658
Filed	: August 21, 1997
Title	: LOW RESISTANCE METAL SILICIDE LOCAL INTERCONNECTS
AND	METHOD OF MAKING
Docket	: MIO 0024 PA
Examiner	: G. Peralta
Art Unit	: 2814

CERTIFICATE OF FACSIMILE TRANSMISSION
I hereby certify that this paper is being facsimile transmitted to the Patent and Trademark Office (Fax. No. 703/872-9318) on March 21, 2003.

Julie G. Cope Reg. No. 48,624

FAX RECEIVED

MAR 2 1 2003

TECHNOLOGY CENTER 2800

Assistant Commissioner for Patents
Washington, D.C. 20231

AMENDMENT

PWALKER
DSASFAI 00000006 09915658
FC:1202 -18.00 OP
FC:1201 -84.00 OP

This amendment is being filed in response to the office action mailed on January 2, 2003. Reconsideration is respectfully requested in light of the amendments and remarks below.

CLEAN VERSION OF THE AMENDMENTS

A version of the amendments showing the markings is provided in a separate appendix attached to this paper.

31. (Amended) A local interconnect comprising:

a composite structure comprising a first metal silicide, a second metal silicide and an intermetallic compound separating said first metal silicide from said second metal silicide, wherein said intermetallic compound comprises metal from said first metal silicide and metal from said second metal silicide, wherein said intermetallic compound contains no non-metallic materials.

35. (Amended) A local interconnect for connecting a first active semiconductor region to a second active semiconductor region on a substrate assembly, said first and second active semiconductor regions being separated by an insulating region, said local interconnect comprising:

PWALKER 00000001 09915658
FC:1202 18.00 OP
FC:1201 84.00 OP

a composite structure comprising a first refractory metal silicide, a second refractory metal silicide and an intermetallic compound separating said first refractory metal silicide from said second refractory metal silicide, wherein said intermetallic compound comprises refractory metal from said first refractory metal silicide and refractory metal from said second refractory metal silicide, said refractory metal from said first refractory metal silicide being different from said refractory metal from said second refractor metal silicide, wherein said intermetallic compound contains no non-metallic materials.

37. (Amended) A semiconductor device comprising:

a substrate assembly having at least one semiconductor layer;

at least one field effect transistor formed in said at least one semiconductor layer, said least one field effect transistor having a source, a drain and a gate; and

a local interconnect for connecting at least one of said source, said drain and said gate to another active area within said substrate assembly, said local interconnect comprising a composite structure comprising a first refractory metal silicide, a second refractory metal silicide and an intermetallic compound separating said first refractory metal silicide from said second refractory metal silicide, wherein said intermetallic compound comprises refractory metal from said first refractory metal silicide and refractory metal from said second refractory metal silicide, wherein said intermetallic compound contains no non-metallic materials.

38. (Amended) A memory array comprising:

a plurality of memory cells arranged in rows and columns and formed on a substrate assembly having at least one semiconductor layer, each of said plurality of memory cells comprising at least one field effect transistor; and

at least one local interconnect for connecting at least one of a source, a drain and a gate of said at least one field effect transistor in one of said plurality of memory cells to one of an active area within said one memory cell or to one of a source, a drain and a gate of said at least one field effect transistor in another one of said plurality of memory cells, said local interconnect comprising a composite structure comprising a first refractory